

GSM <u>ALARM SYSTEM</u>











10.9cm(4.3) TFT Digital Display

Built-in

WIFI / GSM

Telephone Functions

Features:

- Display screen: 10.9cm(4.3) TFT large digital display screen, Date/clock/arm/disarm/cutdown time indication
- Function: Operating system with multitasking design, Automatic alarm indicate when offline
- APP function: App remotely arm/disarm, Parameter setting and accessory management, Rename defence zone
- Learning/storage location: Support up to 100 learning/storage location for remote control and wireless detector
- Record function: Record 20 seconds alarm voice, if alarm occurs the alarm host will dial preset number and play the record voice
- **Network:** Support Wifi/GSM network alarm system, Support different alarm channels (App push/SMS/voice monitoring/center alarm to ensure the alarm performance stable and reliable)
- Telephone function: Support 6 groups preset alarm phone number, SMS on/off and dial on/off can be set respectively, Support SMS alarm/disarm and voice alarm/disarm
- Defence zone supports: Support gate SOS, bedroom, window, balcony, perimeter, smoke, gas, carbon monoxide, water leaking
- Daily operations: Remote control, keyboard, remote SMS, Mobile phone APP, GPRS alarm centre
- Power / Battery: Main power failure/backup battery power shortage
- Tamper Alert Function: Tamper alarm
- APP: Android and IOS can be compatible

(E	F©	RoHS		
3		4		
0				

Secureye Smart APP



Specification	S-AL380	
Power input	DC 5V (micro USB standard interface power supply)	
Working current	<120mA	
Standby current	<80uA	
Alarm current	<500mA	
Wireless frequency	433MHz	
Wireless coding	EV 1527	
GSM bands	850/900/1800/1900MHz	
Wi-Fi bands	IEEE802.11b/g/n RF standard	
Standby battery	3.7V/500mAh lithium-ion	
Temperature range	0°C ~ 55°C	
Humidity range	< 80%RH (No freezing)	
	, , ,	





