

2 MP LPR Pro Bullet Camera



- ▶ Smart Stream, Smart IR II, HCL
- ▶ Integrated Cable Management
- ▶ P-Iris, Defog, 128G

Features:

- 120fps
- License Plate Recognition
- 3 in 1 Super WDR Pro-140dB
- 0.002Lux Ultra Low-light

SPECIFICATION

| | | | |
|-----------------|--|---|--|
| Camera | Image Sensor | 1/2.8" Progressive Scan CMOS | |
| | Min. Illumination | Color: 0.002Lux@F1.2, B/W: 0Lux with IR on | |
| | WDR | 140dB Super WDR (Super WDR Pro is optional for Q Series) | |
| | Lens | Motorized 3.0~10.5mm/2.8~12mm/7~22mm @F1.4, P-Iris(Optional) | |
| | Mount | Φ14 | |
| | Field of View | | H93°~H33°/D107°~D38°/V52°~V18° (3.0~10.5m) |
| | | | H91°~H34°/D105°~D39°/V51°~V19° (2.8~12mm) |
| | | | H40°~H16°/D46°~D19°/V23°~V9° (7~22mm) |
| | Shutter Time | 1/1000000s~1s | |
| | IR Distance | Up to 60m(3.0~10.5mm)/ 100m(7~22mm) | |
| | Day&Night | ICR Filter Auto Switch | |
| | Max. Vehicle Speed | 120km/h | |
| | Max. Image Resolution | 1920x1080 | |
| Video | Primary Stream | 120fps@(1920x1080)(Optional for Q Series), 60fps@(1920x1080, 1280x960, 1280x720, 704x576) | |
| | Secondary Stream | 120fps@(704x576)(Optional for Q Series), 60fps@(704x576, 640x480, 640x360, 352x288, 320x240, 320x192, 320x176) | |
| | Tertiary Stream | 30fps@(1920x1080, 1280x720, 704x576, 640x480, 640x360, 320x240, 320x192, 320x176) | |
| | Video Compression | H.265+/H.265(HEVC)/H.264+/H.264/MJPEG | |
| | Video Bit Rate | 16Kbps~16Mbps(CBR/VBR Adjustable) | |
| | Image Setting | Brightness/Contrast/Saturation/Sharpness | |
| | Audio Network | Ethernet | 1*RJ45 10M/100M Ethernet Port |
| Network Storage | | NAS(Support NFS, SMB/CIFS) | |
| Protocol | | IPv4/IPv6, TCP, UDP, RTP, RTSP, RTCP, HTTP, HTTPS, DNS, DDNS, DHCP, FTP, NTP, SMTP, SNMP,UPnP, SIP, PPPoE, VLAN, 802.1x, QoS, IGMP, ICMP, SSL | |
| Audio | Audio Compression | G.711/AAC | |
| | Audio I/O | 1/1 | |
| | Alarm I/O | 1/1 | |
| System | Storage | Support microSD/SDHC/SDXC Card Local Storage, up to 128G | |
| | Advanced Function | Privacy Masking, Backlight Compensation, HLC, 2D DNR, 3D DNR, ROI, Anti-fog, White Balance, EIS, IP Address Filtering | |
| | SIP/VoIP Support | Yes,Voice & Video-over-IP | |
| | Event Trigger | Motion Detection, Network Disconnection, External Input, Audio Alarm, etc. | |
| | Event Action | FTP Upload, SMTP Upload, SD Card Record, External Output, SIP Phone, HTTP Notification, etc. | |
| | License Plate Recognition | Support | |
| | System Compatibility | ONVIF Profile S & G | |
| General | Working Temperature | -40°C~60°C | |
| | Working Humidity | 0~90%(Non-condensing) | |
| | Power Supply | PoE (802.3af)/ DC 12V±10% | |
| | Power Consumption | 6W MAX 10.5W MAX (With IR on) | |
| | Weather Proof | Up to IP67-rated for Weather-resistant Performance | |
| Housing | Vandal-proof IK10-rated Metal Housing (Optional) | | |

