

Wired **Pet Immunity PIR Sensor**

Features

- · Newly-developed dual element passive infrared sensor unit
- · Wired transmitting digital signal to control panel
- · Intelligent logic control, eliminate false alarm
- Microcontroller temperature analysis and Automatic temperature compensation for best summertime detection
- Tightly-mated bug guard to protect the sensor optics from insects, spiders and dust
- · High immunity to white light
- Selectable detection sensitivity (standard/high) for different environmental requirements
- · SMT adopted, RF and EMI Immunity
- · Adjustable detecting distance
- · Alarm output contacts of relay: N.C./ N.O. optional.

designed to provide detection of criminal intrusion through door frames and window frames into a protected area by sensing infrared energy (heat) emitting from an intruder's body moving through a protected area. The MOTION SENSOR is commonly referred to as a PIR, which stands for passive Infrared. Upon detection of intrusion, the PIR-04 automatically generates an alarm signal to control panel. The sensor also provides a tamper contact output. The unit is RF and EMI Immunity to interferences produced by radio device. The unit is can be wall-mounted by means of a bracket. A special PET IMMUNE MOTION SENSOR is utilized to know the difference between an intruder and a pet.

The wired PIR Motion detector is an INPUT DEVICE, The PIR-04 PIR motion detector is

Specification

| Model | PIR-04 |
|------------------------------|---|
| Operating Voltage | DC9V~16V |
| Detection Range | Vertical angle 60degree, Horizontal angle 110 degree, 12m |
| Standby Current | NC≤15mA; NO≤12mAa |
| Alarm Current | NC < 100mA; NO < 30mA |
| Temper Switch Curren | t NC,12VDC,100mA max |
| RF Immunity | > 25 V/m 10 – 1000 MHz |
| Sensitivity | > 3300V/W |
| White Light Immunity | > 8000 lux |
| Pet Immunity | ≤25Kg |
| Noise(Vp-p) | <200mV, (mVp-p)(25.C) |
| Alarm Output | NC or NO |
| Temperature Range | -5.C to +50.C |
| Relative Humidity | 90% (25 °C) |
| Insta ll ation Mode | Wall mounted by bracket |
| Insta ll ation Height | 2m |
| Housing | High-impact ABS |
| Dimensions | 107x58x39mm(HxWxD) |
| Applications | For indoor use Corridor Office Room Museum |







Applications 4 1 For indoor use. Corridor, Office, Room, Museum, www.secureve.com Library, Finance Room, Warehouse, etc.