

Retractable Dock Shelter (SEDS3400)



KEY FEATURES

- Higher tear resistance.
- Durable side frame construction.
- Maximum sealing from dust ,humidity, temperature.
- Innovative and elegant look.
- Compact Design.
- Flexibility to withstand trailer impact.
- Diverts water entries.
- Shelter is protected by yellow steel guide protectors.
- It allows safe loading and unloading.
- Built-in springs allow the front folding frame to follow the vehicle body, preventing damage to the structure (in the case of incorrect vehicle parking).

SPECIFICATION	SC-S-RDS
Al Frame	50mm X 40mm Rear Frame 45 X 44 mm Front Frame 50 mm X 25 mm X 2.5 mm Brace Front clamping bar 34 mm X 4.8 mm
Front PVC Sheet	Length wise tear resistance more than 550 N Width wise tear resistance more than 900 N Ultimate tensile strength 250N/mm Metal friction coefficient 0.3 PVC friction coefficient 0.4 Thickness 3 mm Specific weight 3.6 kg/m Operation temperature (-35 to +70 °C)
Side PVC Sheet	Tear resistance 250 N Thickness 0.5 m Specific weight 0.7Kg/m Working temperature (-35 to +70 °C) Size 3400 mm X 3400 mm X 600 mm Approx

