

32CH NVR



H.265
Compression

ONVIF

CE FC

RoHS
COMPLIANT

Supported Browser



www.secureeye.com

SPECIFICATION

S-32NV-2HD-265

	Video Input	32CH
Audio / Video	Video Output	VGA 1024×768/1280×1024/1280×800/1440×900/1920×1080@60HDMI 1024×768/1280×1024/1280×800/1440×900/1920×1080@60/3840×2160@30
	Audio Input	Support
	Audio Output	Support
	Video Compression	H.264/H.265
	Video Capacity	32CH 3MP/2MP/1.3MP/1MP & 25CH 5M & 8CH 4K
	Audio Compression	G.711-G.711U
	Live Video	Fullscreen Mode: Main stream Multi Channels Mode: Main stream
Storage	Interface & Capacity	2 SATA (6TB Max.)
	File Format	Log: *.txt/Picture: *.JPG/Video: *.mp4
	Maximum Log	2000
Recording	USB	USB flash disk/external HDD (FAT32)
	Type	Manual/Scheduled/Motion/Alarm
	Playback	2CH 5MP, 4CH 2MP, 1CH 4K
	Playback Control	Last Hr./Next Hr., Last Frame/Next Frame, Backward (8X 16X) Pause/PlaySlow(x1/2 x1/4 x1/8 x1/16)Fast Forward(x2 x4 x8 x16)
Network	Search Mode	By CH/Type/Date (Single or combined)
	Ethernet	10M/100M/1000M
	Max. Remote Channels	64CH
	Protocols Supported	TCP/IP, DHCP, UDP, SMTP, NTP
Interface	Compatibility	ONVIF
	Remote Connection	CMS Client/WebCC/ APP
	Network	1x RJ-45
	USB	3x USB2.0
	Control Device	Mouse
Features	Remote Power Control	Power on/off
	Screen Layout	1/4/8/16/25
	Alarm Actions	Buzzer/Send to Client/alarm email
	Magnification	Support
	USB Recovery	Support
	2Way Communication	Support
	Privacy Mask	Support
	Video Lost Alarm	Support
General	Snapshot on alarm	Support
	Bandwidth	128Mbps I/O bandwidth
	Working Temperature	-10°C ~ 55°C
	Working Humidity	10% ~ 90%
	Power Supply	DC12V
	Power Consumption	≤22W
	Language	Multi Languages
Dimensions(W×H×D)mm	445*45*325	
Weight (g)	≤ 2000g	