



300 MBPS WI-FI 4G LTE ROUTER



Specification		S-4GR200
Air Interface	Technical Standard	Compatible with WCDMA, FDD-LTE , TDD-LTE Default 802.11b/g/n
	Frequency	FDD B1/3/5/8 TDD B40, WCDMA B1/8
	WiFi	2.4G, WIFI 2*2 MIMO , 802.11 b/g/n
	Maximum Data Throughput	LTE CAT 4FDD-LTE(DL/UL) 150Mbps/50Mbps HSPA+(DL/UL) 21/5.76Mbps
Hardware	Receive Diversity	Support Receive Diversity
	MIMO	Support DL 2x2 MIMO
	BB Chipset	ZX297520V3
	WiFi Chipset	RTL8192ES
	WiFi Users	16
	power consumption	<10W
	Power Voltage	DC12V/1A
	USIM/SIM	2FF SIM cardsupport SIM/USIM/UIM,standard 6 PIN SIM card interface, support 3V SIM card and 1.8V SIM card; internal
	LED	Power Indication LED , WiFi Indication LED, LAN/WAN Interface Status LED, Internet Status LED, Signal Strength LED
	Antenna	2 Internal WIFI antenna; 2 External LTE antenna
Software	Buttons	Reset, WPS
	Ethernet	1WAN/LAN + 2LAN, 10BaseT/100Base/ automatic adaptive port
	Reset	Pinhole
	ESD	Contact±8KV, Air±10KV
	SW Update	FOTA(customized) & Local
	WiFi Mode	AP/STATION mode
	WiFi Security	OPEN & WPA-PSK & WPA2-PSK
	SMS & Phone Book	Yes
	UPnP	Need Customize
	IPV4	Support IPV4
Environment	IPV6	Support IPV6
	Firewall	Mac/IP address filter, Port forwarding, WiFi Black/White list
	Data Statistics	Support
	SIM Lock, HTTP, DMZ	
	Operating Temperature	Normal:-10°C to +65°C
Storage Temperature	-20° C to +85° C	
Humidity	5%~ 95%	

