







300 MBPS WI-FI 4G LTE ROUTER



 300 Mb/s Transfer up to 300Mb/s	 Standard Sim Card	 WiFi Protected
 2.4 2.4 GHz	 16 User Connectivity	 Well Compatible

Specification		S-4GVR100
Air Interface	Technical Standard	Compatible with WCDMA, FDD-LTE , TDD-LTE Default 802.11b/g/n
	Frequency	FDD B1/3/5/8 TDD B40, WCDMA B1/8
	WIFI	2.4G, WIFI 2*2 MIMO,802.11 b/g/n/ , 300Mbps
	Maximum Data Throughput	LTE CAT 4 FDD-LTE(DL/UL)150Mbps/50Mbps
Hardware	Receive Diversity	Support Receive Diversity
	MIMO	Support DL 2x2 MIMO
	BB Chipset	ZX297520V3E
	WiFi Chipset	RTL8192ES
	Memory	NAND 1Gbyte; DDR2 512Mbyte
	Power Consumption	<10W
	Power Voltage	DC 12V/1A
	USIM/SIM	2FF SIM card support SIM/USIM/UIM,standard 6 PIN SIM card interface, support 3V SIM card and 1.8V SIM card;internal push-push SIM slot
	LED	Power, Charging, Battery, WAN /LAN, WiFi, 4G/3G
	Antenna	2 external antennas, SMA
	Buttons	Power,Reset
	Ethernet	1WAN+1LAN, 10MBase/100MBase/ automatic adaptive port
	RJ11	Option
	USB	Type-C
	Reset	Pinhole
	ESD	ESD Protection circuit; Contact±8KV, Air±10KV
Software	SW Update	FOTA(customized) TR069
	WIFI Mode	AP/STATION mode
	WIFI Security	OPEN & WPA-PSK& WPA2-PSK
	UPnP	Need customize
	IPV4	Support Ipv4
	IPV6	Support Ipv6
	IPSec	Support
	Firewall	Mac/IP address filter, Port forwarding, WiFi Black/White list
	Data Statistics	
	VPN Pass Through	
Environment	Bandwidth control, SMS & Phone Book SIM Lock, HTTP, DMZ, VoLTE	Support
	Operating Temperature	Normal:-10°C to +65°C
	Storage Temperature	-20° C to +85° C
	Humidity	5%~ 95%

