

Wifi 4 Channel Kit with LCD NVR

S-4MWK



Door Bell



Trigger "Ding Dong" Sound Via Door Bell or LCD



SPECIFICATION

SIP-1S-2HDP-4 (NVR with Monitor)

Operating System	Embedded Linux
Display Size	29.46cm (11.6)
LCD screen Resolution	1366(H)×768(V)
Luminance	220cd/m2
Frequency Range	2.4G WiFi
Cameras Supported	4 Channel
Power Supply	Self - generating
Frequency Range	(Door Bell) 433MHz/315MHz
Ring	25 polyphonic ring tones
System Resources	Simultaneous multi-channel real-time recording, playback, network operation, USB backup
Preview	1/4 Screen
Video Input (CAM)	4 Channels (4*1080P)
Video Compression	H.264
Recording Resolution	720P/960P/1080P
Playback Quality	1080P/960P/720P
Motion Detection	Support
Audio Compression	G.711A
Local Playback	4*720P
Record Storage	HDD Network
Backup Mode	Network backup, USB
Antenna	External Antenna
Network Interface	1*RJ45 10M/100M, self-adaption
USB interface	1*USB2.0 ports
HDD	2.5" HDD Optional 500GB/1TB/2TB
ONVIF	Support
Network Protocol	Support DHCP, DNS, DDNS, NTP, EMAIL, IP searches etc.
Power Supply	DC 12V/2A
Power Consumption	15W (Including HDD)

SIP-1HDG-DIR (2MP Camera)

Resolution	2.0 Megapixel
Sensor	1/3" Sensor
S / N Ratio	> 39.1 dB
Resolution	1920 x 1080 16 : 9
Minimum Illumination	Color: 0.1 Lux B/W: 0.01 Lux
Lens	4mm
OSD	Date Time & Title
Day & Night	Auto / Color / BW
Privacy Regional Shelter	4 Zone Selectable
Smart Stream	Dual-stream: 1920x1080@15fps, 640x480@15fps
Power	DC12V-1A
Power Consumption	≤ 6W
Port	RJ45 / WIFI 802.11b/g/n
Rating	IP65
IR LED	2 Pcs LED & 2 Pcs IR lights
PIR Sensor	Yes
LED light Consumption	2W
IR Distance	6-8 Meters
Working Temp/Humidity	-10°C~50°C / 30% ~ 80% RH
Storage Temp/Humidity	-20°C~60°C / 20% ~ 90% RH