

Face Recognition Fingerprint Reader With Access Control



KEY FEATURES

- ▶ Color 7.1CM (2.8) TFT LCD
- ▶ Face capacity: 1500 (3000 Optional)
- ▶ Fingerprint capacity: 5000 (Optional 10,000 & 50,000)
- ▶ High Resolution Optical Sensor(600 DPI)
- ▶ Support Access Control
- ▶ Communication TCP/IP/Wi-Fi (Optional)/3G

SPECIFICATION	S-FB4K
Camera	Using High - Definition & Dual Camera
Infrared lamps	2 Ultra bright lamp
Fingerprint reader	High Resolution Optical (≥ 600dpi)
Card function	ID Card / Mifare card (Optional)
Display	Color 7.1CM (2.8) TFT LCD
Touch key	16 keys
Human body induction	Yes
LED lamp	Red & Green (Dual Color)
Input port	Wiegand 26/34 (can be external card reader module)
Professional access control	Yes
Communication	TCP/IP, WiFi(Optional), RS485
U disk port	Yes (notice: only support FAT32 file system)
Voice output	Yes
Operating system	LINUX VER3.6.5
Face Capacity	1500 /3000 (Optional)
Fingerprint Capacity	5,000 (Optional 10,000, 50,000)
User record & Management	3,00,000 / 50,000
Access Control	Access control function and optional access / time zone management, Anti - submarien / duress alarm function
Attendance function	Attendance (on/off duty, overtime) time zone
Ring function	Yes
Power management	Sleep function
U disk upload / download	Yes
Registration	Information & record
Dynamic IP allocation	Yes
Algorithm version	Face v2.0
FAR/FRR	0.001% / 1%
Matching speed	< 1 sec.
Intelligent updating function	Yes
Face identification mode	Support 1:N or 1:1
Working Temperature	-10°C ~ 60°C
Working Humidity	20% ~ 80%

