

3MP IP DOME IR CAMERA *with* WiFi



Built-in Mic & Speaker



Motion Detection Alarm



Supports 128GB TF Card



Supports Two-way Audio



3MP Resolution



Features:

- FHD: 3MP, 1296P(2304*1296P), H.264 / H.265
- Audio: Built-in Mic & Speaker, supports two-way audio
- Lens: 4mm Lens, IR range up to 15m
- Storage: MicroSD card (Max 128GB), Local and FTP storage
- AP Hotspot: With wireless access point, camera can be connected to phone directly without router
- Alarm: Support Motion detection alarm, phone push alarm
- Onvif: Support Onvif protocol, can work with NVR
- Software: Support Windows PC(HCMS, Onvif NVR, Blue Iris, ispy), Internet Explorer

Specification

S-IP-3MD-WFA

| | | |
|---------|--|---|
| System | Main Processor | HiSilicon 3516E, High- performance processor |
| | Sensor | 1/2.7", 3Megapixel progressive scan CMOS |
| | Image Compression | H.264 / H.265 (Default is H.264, can be set H.265 by IE browser) |
| Lens | Lens Parameter | Focal length: 4mm, 3MP |
| | Angle of View | Horizontal: 73°, Vertical: 53.6°, Diagonal: 95.2° |
| Video | Resolution | 1296P(2304x1296) / 1080P(1920x1080) / 720P(1280x720) / VGA(640x480) |
| | Image Frame Rate | Main stream: 3MP(15fps - 25fps) / Sub stream: VGA(25fps) |
| | Automatic Exposure | Adjust the image automatically to view clearly |
| | Infrared Mode | Automatic |
| | Night Visibility | 2 PCS array IR illumination LEDs, IR range up to 15 meters |
| | Min.Illuminatioin | 0.01 Lux / F1.2 (With IR Illuminator) |
| | Zoom | App supports 3x digital zoom |
| Audio | Built-in Mic & Speaker, supports two-way audio | |
| Alarm | Alarm | Motion detection alarm |
| | Alarm Notification | Push alarm notifications to your smartphone |
| | Advanced Zone Detection | Set customized motion detection zones to control what you're monitoring |
| Privacy | Privacy Protection | System defaults the first user as administrator, other users accessing the camera need administrator's authorization, otherwise they can't view it. |
| | Privacy Block | Set up to 4 privacy areas |
| Network | Remote Access | P2P |
| | Ethernet | RJ-45 |
| | Wireless | 2.4G IEEE 802.11 b/g/n, supports WEP, WPA & WPA2 Encryption |
| | AP Hotspot | With wireless access point, camera can be connected to phone without router |





www.secureye.com

| | | |
|----------|---------------------|---|
| | Protocol | IPV4, HTTP, HTTPS, TCP/IP, UDP, UPnP, ICMP, IGMP, RTSP, RTP, SMTP, NTP, DHCP, DNS, DDNS, FTP, IP Filter, QoS |
| | Interoperability | Onvif |
| Software | App | iOS & Android |
| | Windows PC CMS | HCMS, ONVIF Device Manager, Blue Iris, ispy etc. |
| | Web Browser | Internet Explorer |
| Record | Record Mode | Motion detection alarm recording, 7/24 recording |
| | Record Standard | HD mode(1296P/1080P/720P) / SD mode(360P) |
| | Storage | MicroSD card (Max 128GB), Local and FTP storage |
| | Playback | Remote and local record playback |
| Other | Product Type | Plastic Dome type, indoor use |
| | Power Supply | DC 12V |
| | Working Temperature | -10°C ~ 50°C |
| | Working Humidity | 10% to 90% RH |
| | Weight | N.W.:232g, G.W.:420g (Note:Actual Weight Final) |
| | Accessories | Adaptor, User Manual, Screws, & LAN Cable |
| | Size | Item size: 118*118*100 mm (LxWxH) Packaging size: 152*135*109mm (LxWxH) |
| | Certification | CE, FCC & RoHS |