

IP Vandalproof Camera



2MP Resolution



18pcs SMD LED



3.6mm Lens



With Smart Function



PoE Supported



H.265+ Compression

Specification		S-IP-D2-VP
Camera	Sensor+DSP	SC2332 + Hi3516EV200
	Sensor	1/3" Progressive scan CMOS Sensor
	Min. Illumination	0.01lux(Color), 0lux(IR on)
	Lens	3.6 mm@F2.0: horizontal FOV: 84°, vertical FOV:44°
	Lens Mount	M12
	IR	9milX18pcs SMD LED
	IR Range	30m
	Smart IR	Support
	Shutter Time	Auto/Manual, 1/3~1/10000s
	Day/Night	IR cut filter with auto switch
	Wide Dynamic Range	DWDR
	Digital noise reduction	2D/3D DNR
	Compression	Video Compression
H.264 Codec profile		Base/Main/High profile
H.265 Codec profile		Main profile
Video Bit Rate		11 Kbps~10 Mbps
Image	Max. Image Resolution	1920 × 1080
	Frame Rate	50Hz: 25fps 1080P(1920 × 1080) 25fps 960P(1280 × 960), 25fps 720P(1280 × 720) 60Hz:30fps 1080P(1920 × 1080), 30fps 960P(1280 × 960), 30fps 720P(1280 × 720)
	Sub Stream	50Hz:25fps D1(704 × 576), 25fps CIF(352 × 288) 60Hz:30fps D1(704 × 480),30fps CIF(352 × 240)
	Image Setting	Brightness/Contrast/Saturation/Hue/Sharpness
	BLC	Support



www.secureye.com

	HLC	Support
	ROI	Support
	Defog	Support
Network	Protocols	TCP/IP,ICMP,HTTP,HTTPS,DHCP,DNS,DDNS,RTP,RTSP,RTCP,NTP,IGMP,UPnP,SMTP,UPnP-TM,P2P,Bonjour,IPV6(NO FTP)
	Event	Motion Detection, Video Shelter
	Smart Functions	Line Crossing, Area Intrusion, Region Entrance, Region Exiting, Fast Moving, Face Detection
	System compatibility	Onvif(Profile S), CGI
	Security	User authentication, IP address filtering, Video mask
	Mobile Surveillance	iPhone, iPad, Android, CMS, WEB
	Communication interface	1 RJ45 10M / 100M Ethernet Port
General	Operating Conditions	-30°C ~ 60°C (-22°F ~ 140°F) Humidity 95% or less (non-condensing)
	Power Supply	DC12V ± 10%
	POE Supply	PoE (802.3af)
	Power Consumption	MAX 8.5W
	Weather Proof	IP66
	Vandalproof	IK10
	Dimensions	∅ 100.6x 88.5(H) mm
	Weight	540g