

2 & 4 Megapixel H.265 Motorized

Network Bullet IR Camera



S-W2SIP-70M / S-W4SIP-70M



















Key Features

- 0.008Lux Starlight
- Super WDR up to 120dB
- H.265 High Efficiency Video Coding
- Integrated Motorized Variforcal Lens(Auto Focus)
- Built-in ICR Filter for Day/Night switching
- Built-in web server for IE/Firefox/Chrome/Sarari preview
- 3D-DNR, Privacy Masking and Motion Detection
- Micro SD/SDHC/SDXC card local storage support
- Built-in efficient IR LEDs, IR distance up to 70m
- Weather-proof IP67-rated Housing
- Built-in 802.3af Compliant PoE
- Support ONVIF Profile S

Supported Browser











Dimension (mm)







IP Video Surveillance Solution

Specification		S-W2SIP-70M	S-W4SIP-70M	
	Image Sensor	1/3" Progressive Scan CMOS		
	Min. Illumination	Color: 0.008Lux @F1.2, B/W: 0Lux with IR on		
Camera	WDR	Super WDR up to 120dB		
	Lens	Motorized 7 ~ 22mm		
	Field of View	H38°~H12°		
	Shutter Time	1/100000s~1/5s		
	IR Distance	Up to 70m		
	Day&Night	ICR Filter Auto Switch		
Video	Max Image Resolution	1920*1080	2592*1520	
		25fps(1920×1080),	20fps(2592×1520),	
		25fps(1280×960),	25fps(2304×1296),	
	Frame Rate	25fps(1280×720),	25fps(1920×1080),	
		25fps(704×576)	25fps(1280×960),	
			25fps(1280×720),	
			25fps(704×576)	
	Video Compression	H.265(HEVC)/H.264/MJPEG		
	Video Bit Rate	16Kbps~16Mbps(CBR/VBR Adjustable)		
	Image Setting	Brightness/Contrast/Saturation/Sharpness		
Network	Ethernet	1*RJ45 10M/100M Ethernet Port		
	Network Storage	NAS(Support NFS, SMB/CIFS)		
	Protocol	TCP/IP, UDP, RTP, RTSP, RTCP, HTTP, HTTPS,		
DNS, DDNS, DHCP, I		DNS, DDNS, DHCP, FTP, NTP, SMTP,	CP, FTP, NTP, SMTP, SNMP, UPnP, SIP, IPv6, PPPoE, VLAN	
System	Storage	Support Micro SD/SDHC/SDXC, up to 64G		
	Advanced Function	Motion Detection, Privacy Masking, Backlight Compensation, 3D-DNR, ROI		
	SIP/VoIP Support	Yes, Voice & Video-over-IP		
	Event Trigger	Motion Detection, Network Disconnection, etc.		
	Event Action	FTP Upload/ SMTP Upload/ SD Card Record/SIP Phone		
	System Compatibility	ONVIF Profile S		
General	Power Supply	PoE/ DC12V±10%		
	Power Consumption	5.5W MAX, 9.5W MAX (With IR on)		
	Weather Proof	Up to IP67 Rating for Weather-resistant		
	Weight	820g		













