



## **KEY FEATURES**

Max. Capacity

- ► H.264 Image Quality
- **▶** 1080P Playback Quality
- > 8ch @ 1080P Video Input

SPECIFICATION	SIP-1S-2HD-8 / SIP-1S-2HD-8P0E
Operating system	Embedded LINUX operating system
System resource	Multi-channel real-time recording synchronously,
	multi-channel real-time
Operating interface	Playback, multi-user network operation, USB backup
Display screen	16-bit true color graphical menu interface & mouse support
Image coding	PAL/NTSC
Image quality	H.264
Playback quality	1080P
Motion detection	Each screen have 192 (16*12) detective area;
	multi-level sensitivity (local channels only)
Record mode	Manual / alarm / dynamic detection / time
Local playback	8/4/1ch
Search mode	Point-in time retrieval, calendar search,
	event search, channel search
Record storage	Local hard disk, network
Backup storage	Network backup, USB Flash Drive, CD-RW
Video input	8ch @ 1080P
Video output	1ch BNC, 1ch VGA, 1ch HDMI
GUI Display	Time, Channel Title, Alarm Status, Recording Status
3G	Supported (On Selected Model)
PoE Port	N/A 8 PoE Port
Email Notification	Yes
Plug & Play DDNS	Yes
IP Filter	Yes
Network interface	RJ45 10M/100M/ adaptive ethernet port
PTZ control	1RS485, 15 kind of PTZ protocols
USB interface	2 USB Port
SATA interface	1 SATA Interface

Each Port Supports Max 4TB HDD







www.secureye.com