

DOME CAMERA



Day-Night
Color/ B&W



SD Card
Support 512GB



iPhone/Android
Support



Motion
Detection



Specification

SIP-4HDG-DIRD

Image Sensor	1/2.5" High-resolution CMOS Sensor
Resolution	5MP
Effective Pixels	2608(H)*1952(V)
Compression	H.264/H.264+/H.265/H.265+/JPEG/AVI /MJPEG
TV System	PAL/NTSC
Electronic Shutter Time	Auto: PAL 1/25-1/10000Sec; NTSC 1/25-1/10000Sec
Minimum Illumination	0.01Lux
S/N Ratio	≥52dB
Scanning System	Progressive
Video Output	Network
Reset Button	Optional
Focus Length	3.6mm
Focus Control / Lens Type	Fixed
Pixels	5MP
Infrared LED	14μ x 18PCS
Infrared Distance	30M
IR Status/IR Power On	Auto Control
Ethernet	RJ-45 (10/100Base-T)
Protocol	TCP/IP,ICMP,HTTP,HTTPS,FTP,DHCP, DNS,DDNS,RTP,RTSP,RTCP,NTP,SMTP
ONVIF	Support ONVIF 2.4
P2P	YES. Support QR Code
POE	Optional/Internal. Support IEEE 802.3af
Video Delay	0.3S (Within the Lan)
Main Stream 1	2592*1944@20fp, 2560*1920@20fp
Main Stream 2	2560*1440@25fp
Main Stream 3	1920*1080@30fps, 1280*720@30fps
Sub Stream 1	720*480@15fps, 720*480@30fps
IE Browser	IE8-11, Google Chrome (lower than Ver44), Firefox (lower than Ver53), Mac Safari (lower than version 12)
Smart Phone	iPhone, iPad, Android, Android Pad
Day/Night	Color/ B&W (IR-CUT)
Image Config	Saturation/Brightness/Contrast /Sharpness, Mirror, 3D NR, White Balance, FLK (Flicker Control)
Corridor Pattern / Defog Mode	Support
ROI /BLC / Motion Detection	Support
WDR	DWDR: 120dB
Privacy Masking	4 Rectangular Zone
Recording Mode	NVR/CMS/Web
Audio	Optional
SD Card Slot	Optional, Support Max 512GB
Housing	Metal ,IP66
IR Cut Filter	YES
Operation Temperature	-20°C~ +60°C RH95% Max
Storage Temperature	-20°C~ +60°C RH95% Max
Power Source	DC12V±10%, 750mA