

3 MP 4G/LAN Dome Camera



4mm Lens



LAN



Onvif



Two Way
Audio



SD Card
Supported

Features:

- 3MP HD resolution
- Support two-way audio, built-in speaker and microphone
- Support Local SD Card and Cloud Storage
- Support humanoid detection, reduce false alarm
- Remotely view by Android, IOS, PC
- Supports RTMP Protocol

Specification

SIP-D3-G

| Specification | SIP-D3-G | |
|---------------|----------------------|--|
| Lens | Size | 4 mm |
| | FOV | 100° |
| Image | Sensor size | 1/2.9" CMOS sensor |
| | Resolution | 3M pixel(2304*1296) |
| | Day-Night mode | IR Light, Auto switch IR-CUT |
| Video | Compression Standard | H.264, H.265 |
| | Frame rate | 15fps |
| | Resolution | 3M (2304*1296) |
| Audio | Input/output | Built in Mic and Speaker (two-way audio) |
| | Compression Standard | AAC |
| Network | 4G Standard | LTE-TDD/LTE-FDD/TD-SCDMA/WCDM |
| | 4G Frequency Band | LET-FDD:B1/B3/B5/B8;LET-TDD:B34/B38/B39/B40/B41; WCDMA:B1/B5/B8 |
| | LAN Port | 10/100 Lan Port Available |
| IR | IR Distance | 20~30m |
| Storage | Local | Support TF card (Max.128G) |
| | Cloud | Support cloud storage |
| Alarm | Smart alert | Humanoid detection, motion detection |
| | Alert information | Notification push to the App |
| General | Power Interface | DC12V |
| | Working temperature | -20°C~50°C |
| | Working humidity | 20%~95% |
| | Protection grade | TVS 4000V lightning protection, surge protection, surge protection |

